

Vacuum Equipment Specialist

Javac Shark Vacuum Pump

- · Javac Shark introduces more than a bold new look to high vacuum pumps- it sets standards previously only available in high end laboratory models.
- Based on the proven Javac VACPAK cartridge, the new Javac Shark proves that good design is not just style; it delivers outstanding performance with real value.
- · Amongst the Shark's many first: it is the first vacuum pump totally enclosed in a tough industrial polypropylene carry case. No more sharp edges, no hot motors, no exposed electrical parts, the easy to carry case does more than look good; it is part of the enhanced functionality.
- Shark is Australian manufactured by Javac, an Australian company with a worldwide reputation for excellence. Javac pumps are approved for military purposes, and also by the United Nations for developing countries.
- Javac is ISO9001 certified, and sells thousands of vacuum pumps into the USA, EU and Asia. With four decades in Australia, Award winning Javac is Australia's largest manufacturer of vacuum pumps and refrigeration recovery equipment.

THE SHARK IS BAC

Shark's revolutionary features:

- Interchangeable VacPak cartridge
- · Fully O-ring sealed

۲

- High performance Gas Ballast
- Built in oil pump and anti suck back
- Factory set tolerances fixed for life
- · Unique construction in blow moulded case
- High vacuum to 10 micron
- 100% Australian design and manufactured
- High water vapour tolerance
- Dual port inlet 1/4 and 3/8 sae flare
- Inlet isolation valve
- Fan cooled 320w motor
- Quiet running, cool to touch
- Looks great
- Easy to carry
- 12 month warranty
- 150/171 litre/min (50/60Hz)
- Fastest * 150litre pump to 15 micron

Specifications:

۲

Nominal Capacity: 162 litre/min @ 50hz, 5.7cfm, 9.7m³/hr 195 litre/min @ 60hz, 6.8cfm, 11.7m³/hr

Speed: 150 litre/min @ 50hz, 5.3cfm, 9.0m³/hr 175 litre/min @ 60hz, 6.2cfm, 10.5m³/hr

> Vacuum: 15, typically - 10 micron

Oil Capacity: 750-800 ml (27 oz)

Dual Stage: configuration, ratio 9:1

Fittings: 1/4 and 3/8 sae flare

Isolation: 1/4 turn valve automatic no oil suck back.

Motor: 0.32 Kw @ 1440 rpm (50hz) 1750 rpm (60hz)

Weight: 12 kg, (26lbs)

Dimensions: 500x300x180mm (LxWxH), 19.6x11.8x7.1 in

۲



۲